

# HP Video HP-1007HD/HDSDI 7" Monitor

## **MONITOR**

- 7" LCD Screen
- High resolution 800 x 480 LCD panel
- Manual Gamma Adjustment
- Adjustable Back light
- Image Flip
- Variety of Markers, including user-adjustable)
- False Color On/Off
- Peaking Filter On/Off
- RGB Check Field / Field Detect
- 15:9, 16:9, 4:3, Pixel-to-Pixel modes
- 4 user-configurable function buttons
- Scratch Resistant Protective Screen
- RGB gain and bias control

## **ANTENNA INPUTS**

- 2 X SMA OR TNC CONNECTORS

## **POWER INPUT**

- 4 PIN XLR connector. Input voltage is 9v to 38v DC, 1.7Amp.
- Auto switching from DCinput to Battery power.

## **BATTERY PLATE**

- The Wireless Monitor comes Variety of Battery Adapters, SONY "L", "M"
- Anton Bauer and V-LOK Plates
- The wireless monitor with Sony "M" size Battery Plate, Works Up to 3.5 Hours With SONY Battery

## **HDMI OUTPUT**

- The Connector is A Type HDMI connector.

## **HD-SDI OUTPUT:**

- 2 x BNC Connectors.

## **OUTPUT SIGNAL FORMATS**

- 480i/59.94
- 567i/50
- 1080i/60
- 1080i/59.94
- 1080i/50
- 1080p/30

- 1080p/29.97
- 1080p/25
- 1080p/24
- 1080p/23.97
- 720p/60
- 720p/59.94
- 720p/50
- 1080p/60 (Picture only)
- 1080p/59.94 (picture only)
- 1080p/50 (picture only)

**THE HD-SDI OUTPUT IS ACTIVE, ONLY WHEN 12V AC/DC POWER SUPPLY IS IN USE**

#### **CHANNELS**

- 10 channels, Automatic select.

#### **LATENCY**

- < 1 millisecond

#### **FREQUENCY**

- 5.1-5.9GHz •

#### **RANGE**

- 200-250 Ft Line Of Sight outdoors
- 100-150 Ft indoor

#### **MONITOR DIMENSIONS**

- 7"(17.7mm) X 5.7(14.5mm) X 3.5(9mm), Without Handles